



# SDS

# GHS Safety Data Sheet

PROFILE Products, LLC

## EcoBlend™

MSDS Number: CON022

Revision Date: 5/17/2016

Page 1 of 5

### 1 PRODUCT AND COMPANY IDENTIFICATION

#### Manufacturer

PROFILE Products, LLC  
750 LAKE COOK ROAD  
SUITE 440  
BUFFALO GROVE, IL 60089

**Contact:** Emergency Phone: (800) 424-9300 (ChemTrec)  
**Phone:** (847) 215-1144  
**Fax:** (847) 215-0577  
**Email:** profileproducts.com  
**Web:** www.profileproducts.com

**Product Name:** EcoBlend™  
**Revision Date:** 5/17/2016  
**MSDS Number:** CON022  
**CAS Number:** Not applicable  
**Product Use:** Erosion control mulch for revegetation and hydraulic seeding

Product Description: Green dyed wood fibers and shredded paper

### 2 HAZARDS IDENTIFICATION

**Route of Entry:** Inhalation, skin contact, eye contact

**Inhalation:** Wood may cause sneezing, irritation, and dryness of the nose and throat. Dust may aggravate pre-existing respiratory conditions.

**Skin Contact:** Wood & paper dust can cause irritation. Skin absorption is not known to occur.

**Eye Contact:** Wood & paper dust can irritate the eyes.

**Ingestion:** No reports of human ingestion.

NFPA: Health = 1, Fire = 1, Reactivity = 0



OSHA Classification: Wood dust is a hazardous substance as defined by the Hazard Communication Standard 29CFR 1910.1200



# SDS

# GHS Safety Data Sheet

PROFILE Products, LLC

## EcoBlend™

MSDS Number: CON022

Revision Date: 5/17/2016

Page 2 of 5

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

**Ingredients:**

Cas #	Perc.	Chemical Name
-----		

### 4 FIRST AID MEASURES

- Inhalation:** Usually not a problem. Remove to fresh air if respiratory irritation develops, and get medical aid promptly if irritation persists.
- Skin Contact:** Usually not a problem. Wash off with running water if irritation is experienced.
- Eye Contact:** Open eyelids and flush with water.
- Ingestion:** Get medical attention.

### 5 FIRE FIGHTING MEASURES

- Flammability:** Combustible product
- Flash Point:** Not applicable
- Flash Point Method:** Not applicable
- Autoignition Temp:** 200-260°C (400-500°F)

Conditions to avoid: In contact with flames or hot surfaces

Flammable- Extinguish with water; same as a wood fire

### 6 ACCIDENTAL RELEASE MEASURES

Scoop up product. Wear goggles and respirator if dust is produced in unventilated areas. Wet product will be slippery.

### 7 HANDLING AND STORAGE

- Handling Precautions:** Clean up areas where dust settles. Minimize blowdown or other practices that generate high airborne dust concentrations.
- Storage Requirements:** Store in a cool, dry place. Keep away from sources of ignition.



# SDS

# GHS Safety Data Sheet

PROFILE Products, LLC

## EcoBlend™

MSDS Number: CON022

Revision Date: 5/17/2016

Page 3 of 5

8

### EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** None required for outdoor mixing and application. Use dust collection system for indoor handling operations.

**Personal Protective Equip:** Eye Protection: Wear goggles when emptying bags and during other operations where there is a risk of dust entering the eyes.  
Gloves: Leather, plastic or rubber gloves could be worn to minimize skin irritation.  
Respirators: When handling methods generate dust at concentrations that exceed occupational exposure limits, wear a NIOSH approved respirator. A fabric respirator or a facepiece respirator with dust cartridges will generally provide adequate protection.  
Footwear: The product is slippery when wet. Wear appropriate footwear.

9

### PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Dyed, green wood & paper fibers - Pine, mixed hardwoods & shredded paper  
**Physical State:** Wood/Paper Fibers  
**Spec Grav./Density:** Lighter than water  
**Vapor Pressure:** N/A  
**Odor:** Mild wood odor

10

### STABILITY AND REACTIVITY

**Stability:** Stable product  
**Conditions to Avoid:** Contact with strong acids and oxidizers may generate heat. Product may ignite at temperatures in excess of 200°C (400°F).  
**Materials to Avoid:** Strong acids and oxidizers  
**Hazardous Polymerization:** Will not occur.

11

### TOXICOLOGICAL INFORMATION

#### EFFECTS OF CHRONIC EXPOSURE:

Inhalation: Frequent and repeated exposure to wood dust is associated with an increased risk of developing nasal cancer.  
Skin Contact: Although rare, wood dust may cause dermatitis in sensitized people.

#### Occupational Exposure Limits:

Wood dusts- All other species: ACGIH (2007): TLV-TWA 1 mg/m<sup>3</sup> (Inhalable fraction); A4

Particulates Not Otherwise Regulated (PNOR): OSHA: PEL-TWA 15 mg/m<sup>3</sup> (Total Dust); 5 mg/m<sup>3</sup> (Respirable fraction)

Irritancy: Wood dust is a mild irritant

Sensitization: Some wood dusts may cause allergic skin reactions



# SDS

# GHS Safety Data Sheet

PROFILE Products, LLC

## EcoBlend™

MSDS Number: CON022

Revision Date: 5/17/2016

Page 4 of 5

12

### ECOLOGICAL INFORMATION

48-hr LC<sub>50</sub> = >100% for Daphnia magna when runoff generated using ASTM D7101 (2"/hr rainfall rate) was tested according to EPA-821-R-02-012.

13

### DISPOSAL CONSIDERATIONS

Normally can be disposed of as a wood residue. Ensure disposal is in compliance with local, provincial (state), and federal regulations.

14

### TRANSPORT INFORMATION

DOT Class: Not regulated #

15

### REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

-----

#### REGULATORY KEY DESCRIPTIONS

-----

MASS = MA Massachusetts Hazardous Substances List  
NRC = Nationally Recognized Carcinogens  
OSHA WAC = OSHA Workplace Air Contaminants  
PA = PA Right-To-Know List of Hazardous Substances  
TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean up substance  
CSWHS = Clean Water Act Hazardous Substances  
EHS302 = Extremely Hazardous Substance  
EPCRAWPC = EPCRA Water Priority Chemicals  
HAP = Hazardous Air Pollutants  
NJ EHS = NJ Extraordinarily Hazardous Substances  
NJHS = NJ Right-to-Know Hazardous Substances  
OSHA PSM = OSHA Chemicals Requiring Process Safety Management  
SARA 313 = SARA 313 Title III Toxic Chemicals



# SDS

# GHS Safety Data Sheet

PROFILE Products, LLC

---

## EcoBlend™

MSDS Number: CON022

Revision Date: 5/17/2016

Page 5 of 5

16

### OTHER INFORMATION